

CONTACT RESISTANCE METER

FEATURES :

- ❖ 4.5 Digits LED display
- ❖ Range : 0 TO 1999.9 $\mu\Omega$ to 199.99m Ω
- ❖ High Measurement Current : 100A DC max.
- ❖ True Four wire resistance measuring technique eliminates lead resistance errors inherent in 2 wire systems.
- ❖ Fully protected against overloads.
- ❖ Proven design

TECHNICAL SPECIFICATIONS: MODEL:CRM 100-1

Display : 4 ½ digits, digital LED display

Resistance Range : 0 - 1999.9 $\mu\Omega$ - 19.999m Ω - 199.99m Ω
 Selectable by a range selector switch

Test current switch : 0 - 100 A DC max

Protection : Electronic type short circuit & overload protection on output.

Meter provided : 4.5 digit, digital resistance meter.

Power : 230V AC, 50 Hz

Type of measurement : 4 Wire Measurement System



TECHNICAL SPECIFICATIONS: MODEL:CRM 100-3

Display : 4 ½ digits, digital LED display

Resistance Range : 0 - 1999.9 $\mu\Omega$ - 19.999m Ω - 199.99m Ω
 Selectable by a range selector switch

Test current switch : 0 - 100 A DC max

Protection : Electronic type short circuit & overload protection on output.

Meter provided : a) 4.5 digit, digital resistance meter.
 : b) 3.5 digit, digital ammeter.
 : b) 3.5 digit, digital DC mV meter.

Power : 230V AC, 50 Hz

Type of measurement : 4 Wire Measurement System